

AIRTEMP 220

Hose Construction

- Tube:** Black, smooth, insulating, EPR rubber compound with very good resistance to high temperature
- Reinforcement:** Synthetic textile fabrics yarns
- Cover:** Black (N), smooth, insulating, wrapped finish EPDM rubber compound, resistant to heat, abrasion, ozone and weather.



Applications

Hot air delivery hose designed for compressors and pneumatic systems like flexible connection between motor blower and road tanker used for dry pellets, abrasive powders and granular material transport.

Temperature Range

-40 °C (-40 °F) to +220 °C (+435 °F)
with peaks to +240 °C (+465 °F)







Tolerances

RMA steel mandrel tolerances

- On inside diameter:** ± 1,59 mm
- On outer diameter:** ± 1,59 mm
- Length tolerance:** ± 1 %

Note

On request also available with clear tube (AIRTEMP 220/WN)

IHXXXXXXXX/XX Part Number/ Standard Length m	 I.D. mm	 O.D. mm	 Working Pressure			 Burst Pressure			 Weight kg/m	 min. Bend Radius mm
			MPa	psi	bar	MPa	psi	bar		
AIRTEMP 220										
IH36346010/40	51	69	1,0	145	10,0	3,0	450,0	30	1,85	350
IH36346011/40	60	78	1,0	145	10,0	3,0	450,0	30	2,13	420
IH36346012/20	65	83	1,0	145	10,0	3,0	450,0	30	2,40	455
IH36346013/20	75	93	1,0	145	10,0	3,0	450,0	30	2,62	550
IH36346014/20	80	98	1,0	145	10,0	3,0	450,0	30	2,65	600
AIRTEMP 220/WN										
IH36346020/40	51	69	1,0	145	10,0	3,0	450,0	30	1,94	350
IH36346021/40	60	78	1,0	145	10,0	3,0	450,0	30	2,26	420
IH36346023/20	75	93	1,0	145	10,0	3,0	450,0	30	2,74	550

Please contact us:

HOSEMANN LTD

www.hosemann.co.uk

office@hosemann.co.uk

RUBBER AIR HOSE AIRTEMP 220 °C – MADE IN ITALY Parker ITR