

DIVER 100 EN 250 N/L

Hose according to EN 250

Hose Construction

- Tube:** Black, smooth, heat and ageing resistant EPDM nitrosamine free rubber compound
- Reinforcement:** Synthetic textile yarns
- Cover:** Black, smooth EPDM nitrosamine free rubber compound, resistant to abrasion, sea water, heat and weathering



Tolerances

- On inside diameter:** $\pm 0,5$ mm
- On outside diameter:** $-0,2 / +0,8$ mm
- Length tolerance:** ± 1 %

Note







Available on request DIVER 100 EN 250 NY/L with yellow cover

Applications

Flexible hose for air supply in scuba diving systems. Designed to exceed the UNI EN 250 standard requirements (point 5,7) flexible hoses for medium pressure, related to tests on loose hoses (not assembled). Hose certified.

Temperature Range

-30 °C (-22 °F) to $+80$ °C ($+176$ °F)

IHXXXXXXXXXX Part Number/ Standard Length m	 I.D. mm	 O.D. mm	 Working Pressure			 Burst Pressure			 Weight kg/m	 min. Bend Radius mm
			MPa	psi	bar	MPa	psi	bar		
IH30310133/100	6,3	12,3	3,5	510,0	35	12,0	1740,0	120	0,12	60
IH30310120/100	6,3	12,5	3,5	510,0	35	12,0	1740,0	120	0,13	60
IH30310132/100	6,4	15,1	3,5	510,0	35	12,0	1740,0	120	0,20	60
IH30310121/100	7,3	13,2	3,5	510,0	35	12,0	1740,0	120	0,12	75
IH30310119/100	7,3	13,5	3,5	510,0	35	12,0	1740,0	120	0,14	75
IH30310126/100	7,3	13,7	3,5	510,0	35	12,0	1740,0	120	0,15	75
IH30310124/80	8	14	3,5	510,0	35	12,0	1740,0	120	0,14	80

Please contact us:

HOSEMANN LTD

www.hosemann.co.uk

office@hosemann.co.uk

WARNING - DO NOT EXCEED 510 psi (35 bar) - HIGHER psi (bar) MAY CAUSE DAMAGE OR PERSONAL INJURY - MEDIUM PRESSURE
- Parker ITR

WARNING - DO NOT EXCEED 510 psi (35 bar) - HIGHER psi (bar) MAY CAUSE DAMAGE OR PERSONAL INJURY - MEDIUM PRESSURE
- Parker ITR