

PRESS® N/R 10

Hose Construction

- Tube:** Black, smooth SBR nitrosamine free rubber compound
- Reinforcement:** Synthetic textile yarns
- Cover:** Black (N), ribbed (/R), abrasion, ageing and weather-resistant SBR/EPDM nitrosamine free rubber compound



Applications

Suitable for discharge of water, compressed air and non-aggressive liquids in many industrial and agricultural applications.

Temperature Range







-30 °C (-22 °F) to +80 °C (+176 °F)

Tolerances

According to UNI EN ISO 1307/97

On inside diameter:

≤ I.D. 5 mm:	± 0,60 mm
I.D. 13 - 19 mm:	± 0,80 mm
I.D. 25 mm:	± 1,20 mm
Length tolerance:	± 1 %

IHXXXXXXXXXX Part Number/ Standard Length m	 I.D. mm	 O.D. mm	 Working Pressure			 Burst Pressure			 Weight kg/m	 min. Bend Radius mm
			MPa	psi	bar	MPa	psi	bar		
IH30301002/100	5	10,5	1,0	150,0	10	3,0	450,0	30	0,10	40
IH30116064/100	13	19	1,0	150,0	10	3,0	450,0	30	0,23	105
IH30111482/80	19	26	1,0	150,0	10	3,0	450,0	30	0,37	150
IH30111481/50	25	33	1,0	150,0	10	3,0	450,0	30	0,54	200

Please contact us:

HOSEMANN LTD

www.hosemann.co.uk

office@hosemann.co.uk

RUBBER AIR HOSE PRESS 10 bar MADE IN ITALY Parker ITR