

MINIERA 10

Hose Construction

- Tube:** Black, oil mist resistant, smooth SBR nitrosamine free rubber compound
- Reinforcement:** Synthetic textile fabrics
- Cover:** Black, abrasion, ageing and weather-resistant SBR nitrosamine free rubber compound



Applications

Suitable for compressed air tools (with minimal oil traces) in factories and designed for quarries, building and mining industries.

Temperature Range

-30 °C (-22 °F) to +80 °C (+176 °F)

Tolerances

RMA steel mandrel

On inside diameter:

≤ I.D. 38 mm: ± 0,79 mm

> I.D. 38 mm: ± 1,59 mm







On outside diameter:

≤ I.D. 19 mm: ± 0,79 mm

I.D. 25 - 102 mm: ± 1,59 mm

Length tolerance:

± 1 %

IHXXXXXXXX/XX Part Number/ Standard Length m	 I.D. mm	 O.D. mm	 Working Pressure			 Burst Pressure			 Weight kg/m	 min. Bend Radius mm
			MPa	psi	bar	MPa	psi	bar		
IH36342180/40	19	29	1,0	150,0	10	3,0	450,0	30	0,56	190
IH36342181/40	25	35	1,0	150,0	10	3,0	450,0	30	0,70	250
IH36342182/40	30	40	1,0	150,0	10	3,0	450,0	30	0,81	300
IH36342183/40	32	42	1,0	150,0	10	3,0	450,0	30	0,85	320
IH36342184/40	35	45	1,0	150,0	10	3,0	450,0	30	0,92	350
IH36342049/40	38	48	1,0	150,0	10	3,0	450,0	30	0,97	380
IH36342185/40	40	50	1,0	150,0	10	3,0	450,0	30	1,02	400
IH36342186/40	45	55	1,0	150,0	10	3,0	450,0	30	1,14	450
IH36342187/40	50	60	1,0	150,0	10	3,0	450,0	30	1,25	500
IH36342188/40	60	70	1,0	150,0	10	3,0	450,0	30	1,47	600
IH36342193/40	63,5	73,5	1,0	150,0	10	3,0	450,0	30	1,52	635
IH36342189/20	70	80	1,0	150,0	10	3,0	450,0	30	1,68	700
IH36342190/20	75	86	1,0	150,0	10	3,0	450,0	30	1,99	750
IH36342191/20	100	112	1,0	150,0	10	3,0	450,0	30	2,86	1000
IH36342194/20	102	114	1,0	150,0	10	3,0	450,0	30	2,99	1020

Please contact us:

HOSEMANN LTD

www.hosemann.co.uk

office@hosemann.co.uk

RUBBER AIR HOSE MINIERA 10 bar MADE IN ITALY Parker ITR