



CARBOPRESS SAE J 200 N/L

Hose Construction

Tube:	Black, smooth, antistatic (R < 1 MΩ/m), NBR rubber compound, resistant to oils, fuels and unleaded petrol, rubber according to SAE J 200 7BG 810 EF11 EF21
Reinforcement:	Synthetic textile yarns
Cover:	Black, smooth, antistatic (R < 1 MΩ/m), NBR/PVC rubber compound resistant to oils, abrasion and weathering



Tolerances

On inside diameter:	± 0,50 mm
On outside diameter:	± 0,60 mm
Length tolerance:	± 1 %

Note

Continuous working at 10 bar and +120 °C (+248 °F) will considerably decrease hose life.

Applications

Hose for lead and unleaded fuels in car and motorbike engines and gearbox lubricants. Hose meets the permeability limits of American Standard SAE 30 R6, SAE30 R7, SAE 30 R8.

Temperature Range

-25 °C (-13 °F) to +120 °C (+248 °F)

IHXXXXXXXXXX Part Number / Standard Length m	 I.D. mm	 O.D. mm	 Working Pressure			 Burst Pressure			 Weight kg/m	 min. Bend Radius mm
			MPa	psl	bar	MPa	psl	bar		
IH30515000/100	4	9	1,0	150,0	10	3,0	450,0	30	0,070	40
IH30515002/100	6	13	1,0	150,0	10	3,0	450,0	30	0,140	55
IH30515003/100	7	13	1,0	150,0	10	3,0	450,0	30	0,127	55
IH30515004/100	7,5	14	1,0	150,0	10	3,0	450,0	30	0,148	65
IH30511035/100	10	16	1,0	150,0	10	3,0	450,0	30	0,165	75

Please contact us:

HOSEMANN LTD

www.hosemann.co.uk

office@hosemann.co.uk

RUBBER FUEL HOSE - INNER TUBE SAE J 200 7 BG 810 EF 11 EF 21 - MADE IN ITALY Parker ITR